ENGLISH



UJBT TIPPER TIE™

KDCR

Automatic Double-Clip Machine



The high speed solution for demanding natural casings and ring-shaped products.

tippertie.com | jbtc.com

TIPPER TIE KDCR Automatic Double-Clip Machine

Area of Application

The KDCR is an automatic double-clip machine specially developed for the production of ring-shaped products in natural ring casings. The machine is ideal for sealing pork and beef rounds in the caliber range up to 46+ mm. Ring-shaped products or shaped products in collagen, cellulose or plastic casings up to caliber 50+ mm can also be processed safely and reliably.

Technology & Function

The KDCR is fast, user-friendly and quiet. It processes up to 130 cycles/ min., depending on the portion size, and has a spool clip magazine. These features leave nothing to be desired in terms of convenience and efficiency.

The special voider system and the moving casing brake ensure careful processing of delicate natural casings. To achieve portions of the same size in terms of appearance, a hand lever control is available as an option. This allows the casings to be filled by sight or by touch in order to compensate for natural deviations of natural casings. The KDCR 75B utilizes the smallest clips from TIPPER TIE (K75 clip family) and has a unique design that allows the shortest sausage tails possible, ideal for small products and rings in natural casings.

The KDCR is maintenance and service friendly. Smooth, stainless surfaces, excellent accessibility to all areas, and inclined horizontal surfaces enable fast, hygienic cleaning. The KDCR complies with all requirements of the clip machine standard EN13885.

Strengths

- Caliber range up to 50 mm
- Number of cycles up to 130 port./min.
- Specially developed for ring-shaped products such as pork sausage, saucisson, ring-shaped salami chorizo, blood sausage and liver sausage
- Gathering protects the casings, and gatherer & clip pressure are individually adjustable
- Pneumatic control
- Two-handed operation increases safety of production personnel
- · Easy to position thanks to sub-frame with castors
- Maintenance-friendly
- Simple, hygienic cleaning

Equipment Versions

- KDCR 75B for short tails
- Casing applicator
- String dispenser for ring-shaped sausage
- Spool clips
- Automatic loop dispenser
- Lever control
- Pneumatically controlled casing brake

Europe

Electric chain counter

North America

TIPPER TIE, INC. 2000 LUFKIN ROAD APEX, NC 27539 USA TEL. +1 919 362 8811 FAX +1 919 362 4839 TipperTie@jbtc.com TIPPER TIE TECHNOPACK GmbH Wilhelm-Bergner-Strasse 9a 21509 Glinde/Germany Tel. +49 40 72 77 04 0 Fax +49 40 72 77 04 100 infoDE@jbtc.com

Latin America

JBT Máq. Equip. Ind. Ltda. Av. Eng. Camilo Dinucci 4605 14808-900 Araraquara São Paulo/Brazil Phone +55 16 3301 2000 Iatinamerica.info@jbtc.com



Lever control for same size portions in terms of appearance.



Spool clips, string loops and string dispensers for efficient production.

Technical Data

Width:	1,045 mm
Depth:	780 mm
Height:	1,800 mm
Weight:	135 kg
Compressed air:	3–6 bar
Clip series KDCR	E200, N200
Clip series KDCR75	K75
Fuse protection:	1 A
Supply voltage:	230V
Sound pressure level:	75 L _{pA} [dB(A)]
	94 L _{wA} [dB(A)]

We're with you, right down the line.[™]

tippertie.com | jbtc.com

DBT TIPPER TIE

KDCR-EN2022-01